



螺紋栓規 **Thread Plug Gauges**



M 公制螺紋 Metric Thread: ISO 6H & 6g (JIS B0251)

單位·mm

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 NP牙長	Fixed	紋栓規 Limit ug Gauges	螺紋環規 GR厚度	螺紋環規 NR厚度	Fixed	紋環規 Limit ng Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
M 2 X 0.4	5	5	1.7415	1.8390	3	3	1.7280	1.6440	•
M 3 X 0.5	5	5	2.6765	2.7840	4	3	2.6620	2.5700	•
M3.5 X 0.6	7	5	3.1115	3.2310	4	3	3.0940	2.9900	•
M 4 X 0.5	5	5	3.6765	3.7840	4	3	3.6620	3.5700	•
M 4 X 0.7	7	5	3.5465	3.6720	6	4	3.5280	3.4190	•
M4.5 X 0.75	7	5	4.0145	4.1400	6	4	3.9960	3.8870	•
M 5 X 0.5	7	5	4.6765	4.7840	4	3	4.6620	4.5700	•
M 5 X 0.8	7	5	4.4815	4.6140	6	4	4.4610	4.3470	•
M 6 X 0.75	7	5	5.5195	5.6560	6	4	5.4960	5.3770	•
M 6 X 1.0	10	7	5,3565	5.5110	8	6	5.3290	5.1980	•
M 7 X 0.75	7	5	6.5195	6.6560	6	4	6.4960	6.3770	•
M 8 X 0.75	7	5	7.5195	7.6560	6	4	7.4960	7.3770	•
M 8 X 1.0	10	7	7.3565	7.5110	8	6	7.3290	7.1980	•
M 8 X 1.25	13	10	7.1945	7.3590	8	6	7.1650	7.0280	•
M 9 X 0.75	7	5	8.5195	8.6560	6	4	8.4960	8.3770	•
M 9 X 1.0	10	7	8.3565	8.5110	8	6	8.3290	8.1980	•
M 10 X 0.75	7	5	9.5195	9.6560	6	4	9.4960	9.3770	•
M 10 X 1.0	10	7	9.3565	9.5110	8	6	9.3290	9.1980	•
M 10 X 1.25	13	10	9.1945	9.3590	8	6	9.1650	9.0280	•
M 10 X 1.5	13	10	9.0325	9.2170	10	8	8.9950	8.8440	•
M 11 X 0.75	10	7	10.5195	10.6560	6	4	10.4960	10.3770	•
M 11 X 1.0	10	7	THE WASHINGTON TO STREET AND ADDRESS.	10.5110	8	6	10.3290		•
M 12 X 1.0	10	7	Contract Con	11.5210	10	8	CONTRACTOR STATE	11.1920	•
M 12 X 1.25	13	10	11.1945	11.3790	10	8	11.1610	11.0100	•
M 12 X 1.5	17	10	11.0325	11.2270	10	8	10.9950	10.8360	•
M 12 X 1.75	17	10	TO STATE OF THE PARTY OF THE PA	11.0740	15	10	10.8300	10.6610	•
M 14 X 1.0	10	7	13.3565	13.5210	10	8	13.3290	13.1920	•
M 14 X 1.5	17	10	13.0325	13.2270	10	8	12.9950	12.8360	•
M 14 X 2.0	17	13	12.7100	12.9270	15	10	12.6640	12.4850	•
M 15 X 1.0	10	7	100000000000000000000000000000000000000	14.5210	10	8	CONTROL PURSUE DO	14.1920	•
M 15 X 1.5	17	10	T. 107 St. 17 ST	14.2270	10	8	13.9950	The second control of	•
M 16 X 1.0	10	7	THE CONTRACTOR STATE	15.5210	10	8	15.3290	15.1920	•
M 16 X 1.5	17	10	and the second second second second	15.2270	10	8	many transfer and a state of the state of th	14.8360	•
M 16 X 2.0	17	13	100000000000000000000000000000000000000	14.9270	15	10	100000000000000000000000000000000000000	14.4850	•
M 17 X 1.0	10	7	70007407457000	16.5210	10	10		16.1920	•
M 17 X 1.5	17	10	\$50000 TO \$5000 TO \$5	16.2270	10	10	1-12-ALDOMESTOCKED	15.8360	•





螺紋栓規 Thread Plug Gauges



M 公制螺紋 Metric Thread: ISO 6H & 6g (JIS B0251)

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 NP牙長	Fixed	紋栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 NR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
M 18 X 1.0	10	7	17.3565	17.5210	10	10	17.3290	17.1920	•
M 18 X 1.5	17	10	17.0325	17.2270	15	10	16.9950	16.8360	•
M 18 X 2.0	17	13	16.7100	16.9270	22	15	16.6640	16.4850	•
M 18 X 2.5	22	17	16.3850	16.6140	22	15	16.3350	16.1460	•
M 20 X 1.0	13	7	19.3565	19.5210	10	10	19.3290	19.1920	•
M 20 X 1.5	17	13	19.0325	19.2270	15	10	18.9950	18.8360	•
M 20 X 2.0	17	13	18.7100	18.9270	22	15	18.6640	18.4850	•
M 20 X 2.5	22	17	18.3850	18.6140	22	15	18.3350	18.1460	•
M 22 X 1.0	13	7	21.3565	21.5210	10	10	21.3290	21.1920	•
M 22 X 1.5	17	13	\$5.74 St. 0.75 St. 1.10 St. 1.50	21.2270	15	10		20.8360	•
M 22 X 2.0	17	13	20.7100	20.9270	22	15	20.6640	20.4850	•
M 22 X 2.5	25	17	20.3850	20.6140	22	15	20.3350	20.1460	•
M 24 X 1.0	13	7	23.3565	23.5310	10	10	23.3290	23.1850	•
M 24 X 1.5	17	13		23.2370	15	10		22.8260	•
M 24 X 2.0	17	13	DESCRIPTION OF THE OWN	22.9390	22	15		22.4750	•
M 24 X 3.0	25	22	and the last back	22.3300	28	22	SECTION AND SECTION ASSESSMENT OF THE PARTY	21.7850	•
M 25 X 1.0	13	10	24.3565	24.5310	10	10	24.3290	24.1850	
M 25 X 1.5	17	13		24.2370	15	10		23.8260	
M 25 X 2.0	22	17	Committee of the Commit	23.9390	22	15	ATTENDED AND DESCRIPTIONS	23.4750	•
M 26 X 1.5	17	13	CONTRACTOR OF THE PARTY OF THE	25.2370	15	10		24.8260	•
M 27 X 1.0	13	10		26.5310	10	10		000000000000000000000000000000000000000	
M 27 X 1.5	17	13		26.2370	15	10		25.8260	•
M 27 X 2.0	22	17	\$20,000 to \$20,000 to \$20,000	25.9390	22	15			
M 27 X 3.0	25	22		25.3300	28	22		24.7850	•
M 28 X 1.0	13	10		27.5310	10	10		27.1850	•
M 28 X 1.5	17	13	Property of the Control of the Contr	27.2370	15	10	A TOTAL POST CONTRACTOR OF THE PARTY OF THE	26.8260	
M 28 X 2.0	22	17	F-120-4-11-20-11-11-11-11-11-11-11-11-11-11-11-11-11	26.9390	22	15		DH-000000000000000000000000000000000000	•
M 30 X 1.0	13	10	100 July 100 100 D	29.5310	15	10	THE RESERVE OF THE PARTY OF THE	29.1850	•
M 30 X 1.5	17	13		29.2370	15	10		28.8260	
M 30 X 2.0	22	17	Description of the Control of the Co	28.9390	22	15	500 C 507 150 150 150	28.4750	
M 30 X 3.0	25	22		28.3300	22	15	Company of the second	27.7850	
M 30 X 3.5	28	25		28.0210	28	22		27.4390	
M 32 X 1.5	17	13		31.2370	15	10			
M 32 X 2.0	22	17		30.9390	22	15		30.4750	
M 33 X 1.5	17	13		32.2370	15	10	All the particular sections of the section of the s	31.8260	
M 33 X 2.0	22	17		31.9390	22	15		31.4750	









M 公制螺紋 Metric Thread: ISO 6H & 6g (JIS B0251)

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 NP牙長	Fixed	紋栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 NR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	備有庫存 in stock
M 33 X 3.5	32	25	30.7360	31.0210	28	22	30.6735	30.4390	
M 35 X 1.5	17	13	34.0325	34.2370	15	10	33.9950	33.8260	•
M 36 X 1.5	17	13	35.0325	35.2370	15	10	34.9950	34.8260	•
M 36 X 2.0	22	17	34.7100	34.9390	22	15	34.6640	34.4750	
M 36 X 3.0	25	22	34.0600	34.3300	28	22	34.0040	33.7850	
M 36 X 4.0	32	25	33.4110	33.7160	38	28	33.3415	33.0950	
M 38 X 1.5	17	13	37.0325	37.2370	15	10	36.9950	36.8260	•
M 39 X 1.5	17	13	38.0325	38.2370	15	10	37.9950	37.8260	
M 39 X 2.0	22	17	37.7100	37.9390	22	15	37.6640	37.4750	
M 39 X 3.0	25	22	37.0600	37.3300	28	22	37.0040	36.7850	
M 39 X 4.0	32	25	36,4110	36.7160	38	28	36.3415	36.0950	
M 40 X 1.5	17	13	39.0325	39.2370	15	10	38.9950	38.8260	•
M 40 X 2.0	22	17	38.7100	38.9390	22	15	38.6640	38.4750	
M 42 X 1.5	17	13	41.0325	41.2370	15	10	40.9950	40.8260	
M 42 X 2.0	22	17	40,7100	40.9390	22	15	40.6640	40.4750	
M 42 X 3.0	32	25	40.0600	40.3300	28	22	40.0040	39.7850	
M 42 X 4.5	40	32	39.0860	39.4060	38	28	39.0135	38.7550	
M 45 X 1.5	17	13	44.0325	44.2370	15	10	43.9950	43.8260	•
M 45 X 2.0	22	17	43.7100	43.9390	22	15	43.6640	43.4750	
M 45 X 4.5	40	32	42.0860	42.4060	38	28	42.0135	41.7550	
M 48 X 1.5	17	13	47.0350	47.2520	15	10	46.9950	46.8160	
M 48 X 2.0	22	17	46.7100	46.9510	22	15	46.6640	46.4650	
M 48 X 5.0	40	32	44.7670	45.1050	40	28	44.6805	44.4080	
M 50 X 1.5	17	13	49.0350	49.2520	15	10	48.9950	48.8160	•
M 50 X 2.0	22	17	48.7100	48.9510	22	15	48.6640	48.4650	
M 50 X 3.0	25	22	48.0600	48.3450	28	22	48.0025	47.7680	
M 52 X 1.5	17	13	51.0350	51.2520	15	10	50.9950	50.8160	
M 52 X 2.0	22	17	50,7100	50.9510	22	15	50.6640	50.4650	
M 52 X 5.0	45	32	48.7670	49.1050	40	28	48,6805	48.4080	
M 55 X 1.5	17	13	54.0350	54.2520	15	10	53,9950	53.8160	
M 55 X 2.0	22	17	53.7100	53.9510	22	15	53.6640	53.4650	
M 56 X 1.5	28	25	55.0350	55.2520	15	10	54.9950	54.8160	
M 56 X 5.5	45	32	52.4430	52.8010	45	38	52.3525	52.0650	
M 58 X 1.5	17	13	57.0350	57.2520	15	10	56.9950	56.8160	
M 60 X 1.5	17	13	59.0350	59.2520	15	10	58.9950	58.8160	
M 60 X 5.5	45	32	56.4430	56.8010	45	38	56.3525	56.0650	

[※]有●者備有庫存。 ● means we have the item in stock.





螺紋栓規 Thread Plug Gauges



M 公制螺紋 Metric Thread: ISO 6H & 6g (JIS B0251)

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 NP牙長	Fixed	紋栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 NR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	 備有庫存 in stock
M 62 X 1.5	17	13	61.0350	61.2520	15	10	60.9950	60.8160	
M 64 X 1.5	17	13		63.2520	15	10	62.9950	62.8160	
M 64 X 6.0	58	45	60.1180	60.4960	50	38	60.0225	59.7200	
M 65 X 1.5	17	13	64.0350	64.2520	15	10	63.9950	63.8160	
M 68 X 1.5	17	13	67.0350	67.2520	15	10	66,9950	66.8160	
M 68 X 6.0	58	45	64.1180	64.4960	50	38		63.7200	
M 70 X 1.5	17	13	69.0350	69.2520	15	10	68.9950	68.8160	
M 75 X 1.5	17	13	74.0350	74.2520	15	10	73.9950	73.8160	
M 76 X 1.5	17	13	75.0350	75.2520	15	10	74.9950	74.8160	
M 80 X 1.5	17	13	\$1.75 (CONTRACTOR OF THE TOTAL	79.2520	15	10	The state of the s	78.8160	
M 80 X 2.0	25	17	78.7100	78.9510	22	15	78.6640	78.4650	
M 80 X 6.0	58	45	76.1180	76.4960	50	38	76.0225	75.7200	
M 82 X 2.0	2.5	17	80.7100	80.9510	22	15	80.6640	80.4650	
M 85 X 2.0	2.5	17	83.7100	83.9510	22	15	ASSESSMENT OF CONTRACTOR	83.4650	
M 85 X 6.0	68	45	E0110 100 200 200 200 200 200 200 200 200	81.4960	60	38		80.7200	
M 90 X 2.0	25	17		88.9510	22	15	CONTRACTOR STATE	88.4650	
M 90 X 6.0	68	45	86.1180	86.4960	60	38	Accompany of the Control of the Cont	85.7200	
M 95 X 2.0	25	17		93.9650	22	15	LEADERS OF BUILDINGS	93.4550	
M 95 X 6.0	68	45	THE CONTRACTOR OF STREET	91.5210	50	38		90.7000	
M100 X 2.0	25	17	98.7100	98.9650	22	15		98.4550	
M100 X 6.0	68	45	96.1180	96.5210	60	38	96.0225	95.7000	
M105 X 2.0	25	17	ENGTONISH OF A SPORT OF	103.9650	22	15		103.4550	
M105 X 6.0	68	45	THE CONTRACTOR OF THE PARTY.	101.5210	50	38	U 5/100 V 35/10 F 60/1 F	100.7000	
M110 X 2.0	25	17	108.7100	108.9650	22	15	108.6640	108.4550	
M110 X 6.0	68	45	106.1180	106.5210	60	38	106.0225	105.7000	
M115 X 2.0	2.5	17		113.9650		15		113.4550	
M115 X 6.0	6.8	45	PERSONAL PROPERTY OF THE PROPERTY OF THE PERSONAL PROPERTY OF THE PERSO	111.5210	60	38		110.7000	
M120 X 2.0	25	17	PROPERTY OF THE PROPERTY OF	118.9650	22	15		118.4550	
M120 X 6.0	68	45	116.1180	116.5210	60	38	NO MARKET CONTRACTOR CONTRACTOR	115.7000	
M125 X 2.0	25	17	123,7100	123.9650	22	15	THE STATE OF THE S	123.4550	
M125 X 6.0	6.8	45		121.5210		38	Charles and Charles and Charles	120.7000	
M130 X 2.0	25	17	Entrangement Company of the Company	128.9650	28	15		128.4550	
M130 X 6.0	68	45	100000000000000000000000000000000000000	126.5210	60	38		125.7000	
M135 X 2.0	25	17		133.9650		15		133.4550	
M135 X 6.0	68	45	\$1000 CONTRACTOR (\$100.00)	131.5210	60	38	THE RESERVE AND ADDRESS OF THE PARTY OF THE	130.7000	
M140 X 2.0	25	17	The state of the s	138.9650	28	15	THE STATE OF THE STATE OF	138.4550	
M140 X 6.0	68	45	The second second	136.5210	60	38		135.7000	
M145 X 2.0	25	17		143.9650	28	15		143.4550	
M145 X 6.0	68	45	PROPERTY OF THE PARTY OF THE PA	141.5210	60	3.8		140.7000	
M150 X 2.0	25	17	The Control of the Co	148.9650	28	15	1. S.	148.4550	
M150 X 6.0	68	45		146.5210	60	38		145.7000	





螺紋栓規 **Thread Plug Gauges**



M 公制螺紋 Metric Thread: JIS Ⅱ (JIS B0251 B0252)

	規格	螺紋栓規 GP牙長	螺紋栓規 WP牙長	Fixed	紋栓規 Limit ug Gauges	GR厚度	螺紋環規 WR厚度	Fixed	紋環規 Limit ing Gauges	Fixed Limit Thread Plug (Ring) Gauges 備有庫存
ol	ecincation	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
M	2 X 0.4	5	5	1.744	1.810	3	3	1.708	1.660	•
M	3 X 0.5	5	5	2.679	2.775	4	3	2.643	2.580	•
M3	.5 X 0.6	7	5	3.114	3.200	4	3	3.068	3.010	•
M	4 X 0.5	5	5	3.679	3.775	4	3	3.633	3.555	•
M	4 X 0.7	7	5	3.549	3.663	6	4	3.511	3.433	•
M4	.5 X 0.75	7	5	4.017	4.113	6	4	3.971	3.893	•
M	5 X 0.5	7	5	4.679	4.775	4	3	4.633	4.555	•
M	5 X 0.8	7	5	4.484	4.605	6	4	4.444	4.361	•
M	6 X 0.75	7	5	5.517	5.613	6	4	5.471	5.393	•
M	6 X 1.0	10	7	5.354	5.470	8	6	5.308	5.220	•
M	7 X 0.75	7	5	6.517	6.613	6	4	6.471	6.393	•
M	8 X 0.75	7	5	7.517	7.633	6	4	7.471	7.383	•
M	8 X 1.0	10	7	7.534	7.470	8	6	7.308	7.220	•
M	8 X 1.25	13	10	7.192	7.318	8	6	7.136	7.038	•
M	9 X 0.75	7	5	8.517	8.633	6	4	8.471	8.383	•
M	9 X 1.0	10	7	8.354	8.470	8	6	8.308	8.220	•
M	10 X 0.75	7	5	9.517	9.645	6	4	9.479	9.393	•
M	10 X 1.0	10	7	9.354	9.480	8	6	9.308	9.210	
M	10 X 1.25	13	10	9.192	10.318	8	6	9.136	9.038	•
M	10 X 1.5	13	10	9.030	9.166	10	8	8.974	8.866	•
M	11 X 0.75	10	7	10.517	10.645	6	4	10.479	10.391	THUR
	11 X 1.0	10	7	10.354	10.480	8	6	10.308	10.210	•
M	12 X 1.0	10	7	11.354	11.490	10	8	11.295	11.190	•
	12 X 1.25	13	10	11.193	11.368	10	8	11.145	11.028	•
-	12 X 1.5	17	10	11.031	11.176	10	8	10.971	10.856	•
	12 X 1.75	17	10	10.867	11.023	15	10	10.801	10.683	
	14 X 1.0	10	7	13.355	13.490	10	8	13.295	13.190	•
	14 X 1.5	17	10	13.031	13.176	10	8	12.971	12.856	•
-1777-	14 X 2.0	17	13	12.705	12.871	15	10	12.639	12.511	•
	15 X 1.0	10	7	14.355	14.490	10	8	14.295	14.190	•
	15 X 1.5	17	10	14.031	14.176	10	8	13.971	13.856	•
	16 X 1.0	10	7	and the Control of the second	15.490	10	8	15.295	15.190	•
	16 X 1.5	17	10	15.031	15.176	10	8	14.971	14.856	•
	16 X 2.0	17	13	14.705	14.871	15	10	14.639	14.511	•
	17 X 1.0	10	7	16.355	16.510	10	10	16.309	16.206	•
	17 X 1.5	17	10	CONTRACTOR STATE	16.216	10	10	15.979	47,1010 White Sc	





螺紋栓規 Thread Plug Gauges



M 公制螺紋 Metric Thread: JIS Ⅱ (JIS B0251 B0252)

	規格 Specification	螺紋栓規 GP牙長	螺紋栓規 WP牙長		紋栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 WR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
	Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	 備有庫存 in stock
1	M 18 X 1.0	10	7	17.355	17.500	10	10	17.295	17.180	•
	M 18 X 1.5	17	10	17.031	17.196	15	10	16.961	16.826	•
1	M 18 X 2.0	17	13	16.706	16.881	22	15	16.636	16.491	•
1	M 18 X 2.5	22	17	16.382	16.566	22	15	16.310	16.166	•
1	M 20 X 1.0	13	7	19.355	19.500	10	10	19.295	19.180	•
7	M 20 X 1.5	17	13	19.031	19.196	15	10	18.961	18.826	•
1	M 20 X 2.0	17	13	18.706	18.881	22	15	18.636	18.491	•
-	M 20 X 2.5	22	17	18.382	18.566	22	15	18.310	18.166	•
	M 22 X 1.0	13	7	21.355	21.500	10	10	21.295	21.180	•
1000	M 22 X 1.5	17	13	21.031	21.196	15	10	20.961	20.826	•
	M 22 X 2.0	17	13	20.706	20.881	22	15	20.636	20.491	•
	M 22 X 2.5	25	17	20.382	20.566	22	15	20.310	20.166	•
	M 24 X 1.0	13	7	23.355	23.500	10	10	23.295	23.180	•
1	M 24 X 1.5	17	13	23.031	23.196	15	10	22.961	22.826	•
	M 24 X 2.0	17	13	22.706	22.891	22	15	22.626	22.481	•
-	M 24 X 3.0	25	22	22.057	22.251	28	22	21.975	21.821	•
1	M 25 X 1.0	13	10	24.355	24.500	10	10	24.295	24.180	•
	M 25 X 1.5	17	13	24.031	24.196	15	10	23.961	23.826	•
1000	M 25 X 2.0	22	17	23.706	23.891	22	15	23.626	23.481	•
4	M 26 X 1.5	17	13	25.031	25.196	15	10	24.961	24.826	•
8	M 27 X 1.0	13	10	26.355	26.520	10	10	26.309	26.199	Vinue •
3	M 27 X 1.5	17	13	26.031	26.196	15	10	25.961	25.826	•
	M 27 X 2.0	22	17	25.706	25.925	22	15	25.648	25.493	•
1	M 27 X 3.0	25	22	25.057	25.251	28	22	24.975	24.821	
	M 28 X 1.0	13	10	27.355	27.500	10	10	27.295	27.180	•
	M 28 X 1.5	17	13	27.031	27.196	15	10	26.961	26.826	•
1	M 28 X 2.0	22	17	26.706	26.891	22	15	26.626	26.481	•
	M 30 X 1.0	13	10	29.355	29.500	15	10	29.295	29.180	•
-	M 30 X 1.5	17	13	29.031	29.196	15	10	28.961	28.826	•
	M 30 X 2.0	22	17	28.701	28.891	22	15	28.626	28.481	
1	M 30 X 3.0	25	22	28.056	28.316	22	15	27.988	27.803	
-	M 30 X 3.5	28	25	27.733	29.947	28	22	27.651	27.477	
1	M 32 X 1.5	17	13	31.031	31.206	15	10	30.961	30.826	•
-	M 32 X 2.0	22	17	30.706	30.901	22	15	30.626	30.471	
	M 33 X 1.5	17	13	32.031	32.206	15	10	31.961	31.826	
1111	M 33 X 2.0	22	17	STATE OF THE STATE OF THE	31.925	22	15		31.493	

[※]有●者備有庫存。





螺紋栓規 **Thread Plug Gauges**



M 公制螺紋 Metric Thread: JIS Ⅱ (JIS B0251 B0252)

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 WP牙長	Fixed	線紋栓規 I Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 WR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
M 33 X 3.5	5 32	25	30.733	30.947	28	22	30.651	30.477	
M 35 X 1.5	5 17	13	34.031	34.206	15	10	33.961	33.826	•
M 36 X 1.5	5 17	13	35.031	35.206	15	10	34.961	34.826	•
M 36 X 2.0	22	17	34.706	34.901	22	15	34.626	34.471	
M 36 X 3.0	25	22	34.056	34.316	28	22	33.988	33.803	
M 36 X 4.0	32	25	33.412	33.632	38	28	33.316	33.132	
M 38 X 1.5	5 17	13	37.031	37.206	15	10	36.961	36.826	•
M 39 X 1.5	5 17	13	38.031	38.226	15	10	37.979	37.844	
M 39 X 2.0	22	17	37.706	37.925	22	15	37.648	37.493	
M 39 X 3.0	1409	22	37.056	37.316	28	22	36.988	36.803	
M 39 X 4.0	000	25	36.408	36.632	38	28		36.132	
M 40 X 1.5	0.000	13	39.031	39.206	15	10	38.961	55/200 CT-0.0 GY956	•
M 40 X 2.0	-	17	38.706	38.901	22	15	38.626	38.471	2.00
M 42 X 1.5	(P (A) P)	13	41.031	41.206	15	10	40.961	40.826	
M 42 X 2.0	200000000000000000000000000000000000000	17	40.706	40.901	22	15			
M 42 X 3.0	2,744.0	25	40.056	40.316	28	22		39.803	
M 42 X 4.5		32	39.083	39.327	38	28		38.797	
M 45 X 1.5	5 -5 (0.01)	13	44.031	44.206	15	10		43.826	
M 45 X 2.0		17	43.706	43.901	22	15			
M 45 X 4.5	100000	32	42.083	42.375	38	28	41.991	41.797	
M 48 X 1.5		13	47.031	47.206	15	10	46.961	46.826	TAUTH THE PARTY OF
M 48 X 2.0	10.4	17	46.706	46.901	22	15	COURT OF THE PARTY	46.471	
M 48 X 5.0	C. 17 10 10 10 10 10 10 10 10 10 10 10 10 10	32	44.758	45.012	40	28	HITCHISON CONTRACTOR	44.452	
M 50 X 1.5	2.11	13	49.031	49.206	15	10	48.961	48.826	
M 50 X 2.0	10000	17	48.706	48.901	22	15	48.626	48.471	
M 50 X 3.0	220000	22	48.056	48.331	28	22	CONTROL OF STREET	PARTITION OF THE PROPERTY OF THE PARTY OF TH	
M 52 X 1.5	VED VED VED	13	51.032	51.216	15	10	The second second second second	50.816	
M 52 X 2.0	G 17779-001	17	50.707	50.911	22	15	100 Page 100	50.461	
M 52 X 5.0		32	48.758	49.087	40	28		48.431	
M 55 X 1.5	W. Fall	13	54.032	54.216	15	10	53.958	53.816	
M 55 X 2.0	13/3/88	17	53.707	53.911	22	15	53.623	53.461	
M 56 X 1.5	3 (39625)	25	55.032	55.238	15	10	54.976	54.834	
M 56 X 5.5		32	52.434	52.783	45	38	52.335	52.088	
M 58 X 1.5	20 10025/00	13	57.032	57.216	15	10		56.816	
M 60 X 1.5	5 T P T S T S T S T S T S T S T S T S T S	13	59.032	59.216	15	10		58.816	
M 60 X 5.5	A CONTRACTOR	32		56.883	45	38	CONCENTRATION OF THE	56.088	

[※]有●者備有庫存。





螺紋栓規 Thread Plug Gauges



M 公制螺紋 Metric Thread: JIS Ⅱ (JIS B0251 B0252)

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 WP牙長	Fixed	紋栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 WR厚度	Fixed	紋環規 Limit ng Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
M 62 X 1.5	17	13	61.032	61.216	15	10	60.958	60.816	
M 64 X 1.5	17	13	63.032	63.216	15	10	62.976	62.834	
M 64 X 6.0	58	45	60.109	60.478	50	38	60.005	59.731	
M 65 X 1.5	17	13	64.032	64.216	15	10	63.958	63.816	
M 68 X 1.5	17	13	67.032	67.216	15	10	66.958	66.816	
M 68 X 6.0	58	45	64.109	64.478	50	38	64.005	63.743	
M 70 X 1.5	17	13	69.032	69.216	15	10	68.958	68.816	
M 75 X 1.5	17	13	74.032	74.216	15	10	73.958	73.816	
M 76 X 1.5	17	13	75.032	75.216	15	10	74.976	74.834	
M 80 X 1.5	17	13	79.032	79.216	15	10	78.958	78.816	
M 80 X 2.0	25	17	78.707	78.921	22	15	78.623	78.461	
M 80 X 6.0	58	45	76.109	76.478	50	38	76.005	75.743	
M 82 X 2.0	25	17	80.708	80.921	22	15	80.620	80.451	
M 85 X 2.0	25	17	83.708	83.921	22	15	83.620	83.451	
M 85 X 6.0	68	45	81.110	81.478	60	38	81.002	80.743	
M 90 X 2.0	25	17	88.708	88.921	22	15	88.620	88.451	
M 90 X 6.0	68	45	86,100	86.478	60	38	86.002	85.743	A Company of
M 95 X 2.0	25	17	93.708	TOURSELY CERTIFIED A	22	15	B2542500354555355060	93.451	
M 95 X 6.0	68	45	91.110	11.20CH190C9A5C	50	38	91.002	E-03884 (04,023836)	
M100 X 2.0	25	17	98.708	98.921	22	15	98.620	98.451	
M100 X 6.0	68	45	96.110	96.503	60	38	96.002	95.723	ZIVII and
M105 X 2.0	25	17	103.708	103.921	22	15	103.620		
M105 X 6.0	68	45	Inches Andreas	101.503	50	38	101.002	The second secon	
M110 X 2.0	25	17	FEMALES AND ASSESSED.	108.921	22	15	108.620	HELD AND THE STREET, S. C.	
M110 X 6.0	68	45	106.110		60	38	106.002	The second second second	
M115 X 2.0	25	17	113.708	113.921	22	15	113.620	113.451	
M115 X 6.0	68	45	111.110	111.503	60	38	111.002	110.723	
M120 X 2.0	25	17	118.708	118.921	22	15	118.620	118.451	
M120 X 6.0	68	45	116.110		60	38	116.002	115.723	
M125 X 2.0	25	17	123.709	123.951	22	15	123.607	123.421	
M125 X 6.0	68	45	121.111	121.503	60	38	120.999		
M130 X 2.0	25	17	128.709	128.951	28	15	128.607	128.421	
M130 X 6.0	68	45	126.111	126.503	60	38	125.999	125.723	
M135 X 2.0	25	17	133.709	A CONTRACTOR AND A CONTRACTOR	28	15	133.607	100 000 000 000 000	
M135 X 6.0	68	45	131.111	131.503	60	38	130.999		
M140 X 2.0	25	17	Device and Say and Table	138.951	28	15	1 THE RESIDENCE OF THE PARTY OF	138.421	

[※]有●者備有庫存。





螺紋栓規 Thread Plug Gauges



M 公制螺紋 Metric Thread: JIS Ⅱ (JIS B0251 B0252)

單位: mm

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 WP牙長	Fixed	級栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 WR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	 備有庫存 in stock
M140 X 6.0	68	45	136.111	136.503	60	38	135.999	135.723	
M145 X 2.0	25	17	143.709	143.951	28	15	143.607	143.421	
M145 X 6.0	68	45	141.111	141.503	60	38	140.999	140,723	
M150 X 2.0	25	17	148.709	148.951	28	15	148.607	148.421	
M150 X 6.0	68	45	146.111	146.503	60	38	145.999	145.723	

W 英制螺紋 British Standard Thread: Ⅱ級(class)、Ⅲ級(class)

單位: mm

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 WP牙長			CD原安	螺紋環規 WR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
Specification	A	В	GO PD	HI PD	С	D	GO PD	LO PD	● 備有庫存 in stock
W 1/8 ы (crest) 40	7	5	2.772	2.860	4	7	2.756	2.688	•
W 5/32 di (crest) 32	7	5	3.465	3,561	4	7	3.465	3.379	•
W 3/16 da (crest) 24	10	7	4.089	4.185	6	10	4.073	3.994	
W 1/4 山 (crest) 20	13	10	5.541	5.647	10	13	5.525	5.427	•
W 5/16 Д (crest) 18	13	10	7.038	7.154	10	13	7.020	6.914	
W 3/8 J. (crest) 16	102.0A0	13	8.513	8.639	10	17	8.497	8.381	•
W 7/16 da (crest) 14	17	13	9.955	10.091	10	17	9.936	9.803	() - O L W
W 1/2 山 (crest) 12	17	13	11.350	11.495	15	17	11.330	11.195	
W 5/8 山 (crest) 11	22	17	14.402	14.576	19	22	14.381	14.236	•
W 3/4 山 (crest) 10	22	17	17.430	17.584	19	22	17.409	17.264	•
W 7/8 di (crest) 9	22	17	20.423	20.598	22	22	20.403	20.248	•
W 1 🔟 (crest) 8	25	17	23.372	23.557	25	25	23.352	23.187	
W 1 1/8 JJ (crest) 7	32	25	26,257	26.442	28	32	26.237	26.062	
W 1 1/4 di (crest) 7	32	25	29.432	29.617	28	32	29.412	29.237	
W 1 3/8 da (crest) 6	42	25	32.220	32.415	38	42	32.199	32.004	
W 1 1/2 山 (crest) 6	42	25	35.395	35.590	38	42	35.374	35.179	

※有●者倘有庫存。

means we have the item in stock.

※無庫存及特殊品,歡迎訂製。 No stock or special specifications are available on request.





螺紋栓規 **Thread Plug Gauges**



UNC 美制粗螺紋 Unified Coarse Thread (ANSI B1.2-2A 2B)

單位· inch

規格 Specification	螺紋栓規 GP牙長 (mm)	螺紋栓規 WP牙長	Fixed	文栓規2B Limit ug Gauges	螺紋環規 GR厚度	螺紋環規 WR厚度	Fixed	文環規2A Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
NO.4 - 40 UNC	7	5	2.433	2.517	4	3	2.413	2.349	•
NO.5 - 40 UNC	7	5	2.763	2.847	4	3	2.743	2.677	•
NO.6 - 32 UNC	7	5	2.994	3.083	4	3	2.957	2.899	•
NO.8 - 32 UNC	7	5	3.654	3.746	6	4	3.615	3.554	•
NO.10 - 24 UNC	7	5	4.142	4.246	6	4	4.100	4.029	•
NO.12 - 24 UNC	7	5	4.803	4.909	6	4	4.760	4.687	•
1/4 - 20 UNC	13	10	5.529	5.648	8	6	5.484	5.403	•
5/16 - 18 UNC	13	10	7.025	7.155	8	6	6.978	6.889	•
3/8 - 16 UNC	13	10	8.498	8.638	12	8	8.448	8.349	•
7/16 - 14 UNC	13	10	9.938	10.088	12	8	9.886	9.779	•
1/2 - 13 UNC	17	13	11.434	11.595	15	10	11.380	11.265	•
9/16 - 12 UNC	22	17	12.918	13.086	22	15	12.861	12.741	•
5/8 - 11 UNC	22	17	14.381	14.559	22	15	14.323	14.197	
3/4 - 10 UNC	25	17	17.403	17.594	22	15	17.341	17.204	•
7/8 - 9 UNC	32	25	20.396	20.599	22	15	20.330	20.183	•
1 - 8 UNC	32	25	23.343	23.561	28	22	23.271	23.114	•
1 1/8 - 7 UNC	32	25	26.223	26.456	28	22	26.147	25.980	A 11.
1 1/4 - 7 UNC	32	25	29.398	29.636	28	22	29.322	29.150	•
1 3/8 - 6 UNC	32	25	32.180	32.438	28	22	32.098	31.911	
1 1/2 - 6 UNC	32	25	35.355	35.615	28	22	35.273	35.083	
1 3/4 - 5 UNC	40	32	41.157	41.445	32	28	41.063	40.856	
2 - 4 1/2 UNC	40	32	47.141	47.449	32	28	47.042	46.820	
2 1/4 - 4 1/2 UNC	40	32	53.491	53.804	32	28	53.392	53.165	
2 1/2 - 4 UNC	40	32	59.382	59.717	32	28	59.277	59.033	
2 3/4 - 4 UNC	40	32	65.732	66.073	36	28	65.624	65.378	
3 - 4 UNC	40	32	72.082	72.428	36	28	71.974	71.722	
3 1/4 - 4 UNC	40	32	78.432	78.783	36	28	78.322	78.065	
3 1/2 - 4 UNC	40	32	84.782	85.138	36	28	THE THEORY CHARLES AND ADMINISTRA	84.412	
3 3/4 - 4 UNC	40	32	91.132	91.493	38	28	71199 TOO TOO SOL	90.755	
4 - 4 UNC	40	32	97.482	97.848	38	28	97.369	97.102	

※有●者備有庫存。

※無庫存及特殊品, 歡迎訂製。 No stock or special specifications are available on request.

means we have the item in stock.





螺紋栓規 Thread Plug Gauges



UNF 美制細螺紋 Unified Fine Thread (ANSI B1.2-2A 2B)

單位: inch

規格	螺紋栓規 GP牙長	螺紋栓規 WP牙長 (mm)	Fixed	放栓規2B Limit lug Gauges	螺紋環規 GR厚度 (mm)	螺紋環規 WR厚度	Fixed	文環規2A Limit ing Gauges	Fixed Limit Thread Plug (Ring) Gauges	
Specification	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock	
NO.4 - 48 UNF	7	5	2.501	2.580	6	4	2.484	2.423	•	
NO.5 - 44 UNF	7	5	2.799	2.880	6	4	2.781	2.717	•	
NO.6 - 40 UNF	7	5	3.097	3.180	6	4	3.065	3.008	•	
NO.8 - 36 UNF	7	5	3.712	3.799	6	4	3.680	3.617	•	
NO.10 - 32 UNF	7	5	4.315	4.409	6	4	4.275	4.212	•	
NO.12 - 28 UNF	7	5	4.902	5.003	6	4	4.859	4.791	•	
1/4 - 28 UNF	10	7	5.761	5.869	8	6	5.723	5.652	•	
5/16 - 24 UNF	10	7	7.254	7.371	8	6	7.209	7.128	•	
3/8 - 24 UNF	13	10	8.841	8.961	10	8	8.796	8.713	•	
7/16 - 20 UNF	13	10	10.291	10.424	10	8	10.242	10.147	•	
1/2 - 20 UNF	13	10	11.879	12.016	10	8	11.829	11.732	•	
9/16 - 18 UNF	17	13	13.375	13.520	15	10	13.323	13.221	•	
5/8 - 18UNF	17	13	14.963	15.110	15	10	14.910	14.804		
3/4 - 16 UNF	17	13	18.023	18.183	15	10	17.968	17.854	•	
7/8 - 14 UNF	25	13	21.051	21.224	15	10	20.993	20.869	•	
1 - 12 UNF	25	13	24.030	24.218	15	10	23.968	23.831	•	
1 1/8 - 12 UNF	25	13	27.205	27.298	15	10	27.143	27.003	A West	
1 1/4 - 12 UNF	25	17	30.380	30.579	19	15	30.318	30.173	•	
1 3/8 - 12 UNF	25	17	33.555	33.759	19	15	33.490	33.343	•	
1 1/2 - 12 UNF	25	17	Proceedings of the Control	36.936	19	15		36.516	DAME OF	

※有●者備有庫存。

means we have the item in stock.

※無庫存及特殊品,數迎訂製。 No stock or special specifications are available on request.





螺紋栓規 Thread Plug Gauges



UNEF 美制極細螺紋 Unified Extra Fine Thread (ANSI B1.2-2A 2B)

單位: inch

規格 Specification	螺紋栓規 GP牙長 (mm)	螺紋栓規 WP牙長			螺紋環規 GR厚度 (mm)	螺紋環規 WR厚度	Fixed	文環規2A Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
NO.12 - 32 UNEF	7	5	0.1957	0.1998	8	6	0.1948	0.1917	•
1/4 - 32 UNEF	10	7	0.2297	0.2339	8	6	0.2287	0.2255	
5/16 - 32 UNEF	10	7	0.2922	0.2964	8	6	0.2912	0.2880	•
3/8 - 32 UNEF	10	7	0.3547	0.3591	8	6	0.3537	0.3503	•
7/16 - 28 UNEF	10	7	0.4143	0.4189	10	8	0.4132	0.4096	•
1/2 - 28 UNEF	10	7	0.4768	0.4816	10	8	0.4757	0.4720	•
9/16 - 24 UNEF	17	13	0.5354	0.5405	10	8	0.5342	0.5303	•
5/8 - 24 UNEF	17	13	0.5979	0.6031	10	8	0.5967	0.5927	•
3/4 - 20 UNEF	17	13	0.7175	0.7232	15	10	0.7162	0.7118	
13/16 - 20 UNEF	17	13	0.7800	0.7857	15	10	0.7787	0.7743	•
7/8 - 20 UNEF	17	13	0.8425	0.8482	15	10	0.8412	0.8368	•
15/16 - 20 UNEF	17	13	0.9050	0.9109	15	10	0.9036	0.8991	•
1 - 20 UNEF	17	13	0.9675	0.9734	15	10	0.9661	0.9616	•
1 1/16 - 18 UNEF	17	13	1.0264	1.0326	15	10	1.0250	1.0203	•
1 1/8 - 18 UNEF	17	13	1.0889	1.0951	15	10	1.0875	1.0828	•
1 3/16 - 18 UNEF	17	13	1.1514	1.1577	15	10	1.1499	1.1450	•
1 1/4 - 18 UNEF	17	13	1.2139	1.2202	15	10	1.2124	1.2075	•
1 5/16 - 18 UNEF	17	13	1.2764	1.2827	15	10	1.2749	1.2700	•
1 3/8 - 18 UNEF	17	13	1.3389	1.3452	15	10	1.3374	1.3325	
1 7/16 - 18 UNEF	17	13	1.4014	1.4079	15	10	1.3999	1.3949	•
1 1/2 - 18 UNEF	17	13	1.4639	1.4704	15	10	1.4624	1.4574	•
1 9/16 - 18 UNEF	17	13	1.5264	1.5329	15	10	1.5249	1.5199	
1 5/8 - 18 UNEF	17	13	1.5889	1.5954	15	10	1.5874	1.5824	
1 11/16 - 18 UNEF	17	13	1.6514	1.6580	15	10	1.6499	1.6448	

UNS 美制特殊螺紋 Unified Special Thread (2A 2B)

單位: inch

規格 Specification	螺紋栓規 GP牙長 (mm) A	螺紋栓規 WP牙長 (mm)	Th. A T L. A.		GR厚度	螺紋環規 WR厚度	Fixed	文環規2A Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
		В	GO PD	HI PD	(mm)	D (mm)	GO PD	LO PD	● 備有庫存 in stock
NO.10 - 28 UNS	7	5	0.1668	0.1711	6	4	0.1658	0.1625	•
NO.12 - 48 UNS	7	5	0.2025	0.2059	6	4	0.2017	0.1991	•
1/4 - 27 UNS	10	7	0.2259	0.2304	8	6	0.2249	0.2214	•
5/16 - 27 UNS	10	7	0.2884	0.2929	8	6	0.2874	0.2839	•
3/8 - 27 UNS	10	7	0.3509	0.3556	8	6	0.3498	0.3462	•
7/16 - 24 UNS	10	7	0.4104	0.4153	8	6	0.4093	0.4055	•
7/16 - 27 UNS	10	7	0.4134	0.4181	8	6	0.4123	0.4087	•
1/2 - 27 UNS	10	7	0.4759	0.4807	8	6	0.4748	0.4711	•

[※]有●者備有庫存。

means we have the item in stock.





螺紋栓規 Thread Plug Gauges



UNS 美制特殊螺紋 Unified Special Thread (2A 2B)

單位: inch

規格 Specification	螺紋栓規 GP牙長 (mm)	螺紋栓規 WP牙長	Fixed	效栓規2B Limit lug Gauges	螺紋環規 GR厚度 (mm)	螺紋環規 WR厚度	Fixed	效環規2A Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauge
	A	В	GO PD	HI PD	C		GO PD	LO PD	● 備有庫存 in stock
9/16 - 27 UNS	10	7	0.5384	0.5432	8	6	0.5376	0.5336	•
5/8 - 27 UNS	10	7	0.6009	0.6059	8	6	0.5998	0.5960	•
3/4 - 27 UNS	10	7	0.7259	0.7310	8	6	0.7247	0.7208	•
7/8 - 24 UNS	13	10	0.8479	0.8532	10	8	0.8467	0.8426	•
15/16 - 24 UNS	13	10	0.9104	0.9159	10	8	0.9091	0.9049	•
1 - 14 UNS	13	10	0.9536	0.9609	10	8	0.9519	0.9463	•
1 1/8 - 24 UNS	13	10	1.0979	1.1034	10	8	1.0966	1.0924	
1/4 - 24 UNS	13	10	1.2229	1.2285	10	8	1.2216	1.2173	
1 3/8 - 24 UNS	13	10	1.3479	1.3535	10	8	1.3466	1.3423	
1/2 - 24 UNS	13	10	1.4729	1.4787	10	8	1.4716	1.4672	
5/8 - 24 UNS	13	10	1.5979	1.6037	10	8	1.5966	1.5922	
1 3/4 - 18 UNS	17	13	1.7139	1.7205	15	10	1.7124	1.7073	
7/8 - 18 UNS	17	13	1.8389	1.8455	15	10	1.8374	1.8323	
2 - 18 UNS	17	13		1.9706	15	10	1.9624	1.9573	
2 1/16 - 16 UNS	17	13	2.0219	2.0289	15	10	2.0203	2.0149	
2 3/16 - 16 UNS	17	13	2.1469	2.1539	15	10	2.1453	2.1399	
2 1/4 - 18 UNS	17	13	2.2139	2.2206	15	10	2.2124	2.2073	人物社业
2 5/16 - 16 UNS	17	13		2.2791	15	10	2.2702	2.2647	
2 1/2 - 18 UNS	17	13		2.4708	15	10	2.4623	2.4570	
2 3/4 - 18 UNS	17	13		2.7208	15	10	100 000 NATE ON STANSON	2.7070	
3 - 18 UNS	17	13	2.9639	2.9709	15	10	2.9623	2.9569	
3 1/4 - 18 UNS	17	13		3.2209	15	10	3.2123	3.2069	
3 1/2 - 18 UNS	17	13	3.4639	FYSSIASC TESTS	15	10	ELECTRONIC SEC-1000000	3.4567	
3/4 - 18 UNS	17	13	3.7139	3.7211	15	10	3.7122	3.7067	
1 - 14 UNS	22	17	3.9536	3.9616	15	10	3.9518	3.9456	
1/4 - 14 UNS	22	17	4.2036	4.2116	15	10	4.2018	4.1956	
1/2 - 14 UNS	22	17	4.4536	100 PM 100 PM 100 PM 100 PM	15	10	4.4518	4.4456	
3/4 - 14 UNS	22	17	4.7036	4.7119	15	10	4.7017	4.6953	
5 - 14 UNS	22	17	17-10-10-12-12-1	4.9619	15	10	4.9517	4.9453	
5 1/4 - 14 UNS	22	17		5.2119	15	10	5.2017	5.1953	
5 1/2 - 14 UNS	22	17		5.4619	15	10		5.4453	
5 3/4 - 14 UNS	22	17		5.7121	15	10	THE PROPERTY OF THE PARTY OF TH	5.6951	
6 - 14 UNS	22	17	5.9536		15	10		5.9451	

[※]有●者備有庫存。

means we have the item in stock.





螺紋栓規 Thread Plug Gauges



BC 自轉車用 Bicycle: JIS B0225

單位: mm

規格	螺紋栓規 GP牙長				螺紋栓規 WP牙長	Fixed	i紋栓規 Limit lug Gauges	螺紋環規 GR厚度	螺紋環規 WR厚度	Fixed	紋環規 Limit ing Gauges	限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
Spec	Specification A	A	В	GO PD	HI PD	C	D	GO PD	LOPD	備有庫存 in stock		
BC 5/16	ப்(crest) 26	10	7	7.425	7.550	8	6	7.405	7.290	•		
BC 3/8	山(crest) 26	10	7	9.015	9.140	8	6	8.995	8.880	•		
BC 7/16	山(crest) 26	10	7	10.595	10.720	8	6	10.575	10.460			
BC 1/2	Jı (crest) 20	17	13	12.025	12.160	10	8	12.005	11.880	•		
BC 9/16	ц(crest) 20	17	13	13.615	13.750	10	8	13.595	13.470	•		
BC 5/8	ப்(crest) 20	17	13	15.205	15.340	10	8	15.185	15.060	•		
BC 11/16	山(crest) 24左	17	13	16.906	17.040	10	8	16.882	16.760	•		
BC 3/4	ப்(crest) 30	13	10	18.606	18.740	8	6	18.582	18.460			
BC 31/32	ப்(crest) 30	13	10	24.166	24.300	8	6	24.142	24.020			
BC 1	di (crest) 24	17	13	24.848	25.000	10	8	24.816	24.680	•		
BC 1 1/8	ப்(crest) 26	13	10	28.063	28.215	10	8	28.031	27.895			
BC 1 1/4	ப்(crest) 26	13	10	31.238	31.390	10	8	31.206	31.070			
BC 1.37	.ப்(crest) 24	17	13	34.248	34.410	10	8	34.216	34.070	•		
BC 1.42	dı (crest) 24	17	13	35.516	35.678	10	8	35.484	35.338			
BC 1 7/16	di (crest) 24	17	13	35.958	36.120	10	8	35.926	35.780			
BC 1.45	山(crest) 24	17	13	36.278	36.440	10	8	36.246	36.100			
BC 1 9/16	ப்(crest) 24	1.7	13	39,138	39.300	10	8	39,106	38.960	MILITARY - TOTAL		

SM 針車用 Sewing Machine: JIS II 級(class) (JIS B0226

	螺紋栓規 GP牙長	螺紋栓規 WP牙長			it CD層度	螺紋環規 WR厚度	限界螺紋環規 Fixed Limit Thread Ring Gauges		限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
	A	В	GO PD	HI PD	C	D	GO PD	LO PD	● 備有庫存 in stock
SM 1/8 Д (crest) 40	7	5	2.767	2.853	4	3	2.751	2.673	•
SM 1/8 .L(crest) 44	7	5	2.804	2.890	4	3	2.788	2.710	•
SM 1/8 Jr (crest) 48	7	5	2.835	2.921	4	3	2.819	2.725	•
SM 9/64 da(crest) 40	7	5	3.164	3.250	6	4	3.148	3.070	•
SM 11/64 Д (crest) 40	7	5	3.958	4.054	6	4	3.942	3.854	•
SM 3/16 da (crest) 28	10	7	4.174	4.273	8	6	4.158	4.070	•
SM 15/64 da(crest) 28	10	7	5.368	5.474	8	6	5.352	5.254	•
SM 1/4 Дг(crest) 24	10	7	5.667	5.773	8	6	5.651	5.553	•
SM 1/4	10	7	5.765	5.871	8	6	5.749	5.651	•
SM 1/4 Jr(crest) 40	10	7	5.942	6.048	6	4	5.926	5.828	•
SM 9/32 da (crest) 20	13	10	6.323	6.439	10	8	6.307	6.199	•
SM 9/32 дь(crest) 28	10	7	6.559	6.675	8	6	6.543	6.435	•

[※]有●者備有庫存。



限界螺紋栓(環)規

Fixed Limit Thread Plug (Ring) Gauges



螺紋栓規 Thread Plug Gauges



SM 針車用 Sewing Machine: JIS Ⅱ級(class) (JIS B0226)

規格 Specification	螺紋栓規 GP牙長	螺紋栓規 WP牙長	限界螺紋栓規 Fixed Limit Thread Plug Gauges		螺紋環規 GR厚度	螺紋環規 WR厚度	W15		限界螺紋栓環規 Fixed Limit Thread Plug (Ring) Gauges
	A	В	GO PD	III PD	C	D	GO PD	LOPD	備有庫存 in stock
SM 5/16 山(crest) 18	17	13	7.026	7,142	8	6	7.010	6.902	
SM 11/32 بل (crest) 28	10	7	8.146	8.262	8	6	8.130	8.022	
SM 3/8 d (crest) 18	17	13	8.613	8.739	8	6	8.597	8.479	
SM 3/8 Ju (crest) 28	10	7	8.940	9.056	8	6	8.924	8.816	
SM 7/16 Д (crest) 16	17	13	10.085	10.221	8	6	10.069	9.941	1
SM 7/16 di (crest) 28	10	7	10.527	10.653	8	6	10.511	10.393	
SM 1/2 db(crest) 28	10	7	12.115	12.251	8	6	12.099	11.971	
SM 9/16 da (crest) 20	13	10	13.467	13.613	10	8	13.451	13.313	